



OEM

Fujitsu F53 & F56

The small footprint family.



Fujitsu F53



Fujitsu F56

- Small footprint
- Minimal maintenance required
- Intelligent design for long life
- Front service
- Rear service
- Spray or bundle presentation
- Dual presentation

ARCA

1151 Holmes Rd, Mebane, NC 27302 | +1 919 442 5200
arcatechsystems.com | info@arcatechsystems.com



OEM

Fujitsu F53 & F56

Specifications

Dimensions (W x D x H) 2-denominations	F53	6.30" x 13.82" x 12.99" (160 mm x 351 mm x 330 mm)
	F56	6.30" x 15.63" x 14.76" (160mm x 397mm x 375mm)
	Cassette	4.57" x 8.50" x 3.86" (116 mm x 216mm x 98 mm)
Weight (W/O media)	F53	18.74 lbs (8.5 kg)
	F56	24.25 lbs (11 kg)
	Cassette	1.54 lbs (0.7 kg)
Service Access		Front, Rear or Dual
Number of Cassettes		Up to 6 Cassettes
Bill Count Speed		2 Notes / Second
Media Specs	Dimensions	F53 Max. 3.23" x 6.50" (82 mm x 165 mm) Min. 2.36" x 4.72" (60 mm x 120 mm)
		F56 Max. 3.23" x 6.30" (82 mm x 160 mm) Min. 2.36" x 4.72" (60 mm x 120 mm)
	Thickness	
Bills / Transaction		20 Bills / Transaction
Bill Retrieval	F53	None
	F56	Option
Shutter	F53	None
	F56	Option
Capacities / Denominations		Accommodation 2.36" (60 mm) New US Note 500 each cassette (approx.)
Standard		UL, TUV certified
Reject Bill Area Capacity		20 bills
Bill Low Sensor		Fixed Sensor 40 Notes each cassette (approx.)
Interface		RS232C
Electrical Power Requirements	F53	DC +24V +-10%, Max. 6A, Ave. 4A
	F56	DC +24V +-10%, Max. 7A, Ave. 5A
Temperature	Operation	32° F - 104° F (0° C - 40° C)
	Stop State	-23° F - 122° F (-5° C - 50° C)
Relative Humidity	Operation	10% - 95%
	Stop State	8% - 95%